



Járható
megoldások

Click Vinyl Floor





 Járható megoldások		Click Vinyl Floor		
Product Specification				
Item	-----	Unit	Requirement	Result
Total Thickness	-----	MM	-----	4.2
Wear Layer	-----	MM	-----	0.5
Surface Treatment	-----	MM	-----	PUR
Size(LxW)	-----	MM	-----	600.6*295.3 177.8*1219.2
Technical Characteristics		EN standard Temperature: 23 °C ±2 °C / EN standard Humidity: 50%±5%		
Item	Standard	Unit	Result	
Length/Width	EN427	mm	≤0.13% ≤0.50mm	
Squareness/Straightness	EN427	mm	≤0.25mm	
Total thickness	EN428	mm	±0.15mm	
Wear layer	EN429	mm	±0.02mm	
Middle/back layer	EN429	mm	±0.01mm	
Total mass per unit area	EN 430	----	Nominal value +13% / -10%	
Peeling Strength of layer	EN431	----	>50N/50mm	
Residual indentation(average)	EN433	mm	<0.1	
Sound, impact, reduction	EN ISO 717-2	dB	>4.8	
Fire Resistance	EN13501-1	----	Bfl-S1	
Dimension stability after exposure to heat	EN434	%	<0.25	
Curing after exposure to heat	EN434	mm	<1.2mm	
Color fastness to light	ISO105 B02	----	grade>6	
Loss on heating	JIS A5705	----	<0.5%	
Change in length to water absorption	JIS A5705	mm	<0.20mm	
Flexibility	EN435	----	pass	
Abrasion resistance	EN660	----	Class T	
Castor Chair resistance	EN425	----	Pass	
Slip resistance	EN13893	----	Class DS	
Chemical resistance	EN423	----	Pass	
Bearing a castor chair	EN425	----	pass	
Toxicity	EN71-3	----	pass	
Performance Classification	EN 685	----	33/42	
Underfloor heating suitable		----	suitable	
Recycle		----	suitable	
Warranty		----	Residential---25 Years	
		----	Commercial-Moderate/General Use---5Years	
VOC(volatile organic compound) requirements by DIBT from Europe(Germany) for use in residential&commercial environment&contributes to GOOD IAQ(indoor air quality)				



PACKAGE UNIT: 12PCS/CARTON